UNCLASSIFIED AD 414835

DEFENSE DOCUMENTATION CENTER

FOR


SCIENTIFIC AND TECHNICAL INFORMATION

CAMERON STATION, ALEXANDRIA, VIRGINIA



UNCLASSIFIED

NOTICE: When government or other drawings, specifications or other data are used for any purpose other than in connection with a definitely related government procurement operation, the U. S. Government thereby incurs no responsibility, nor any obligation whatsoever; and the fact that the Government may have formulated, furnished, or in any way supplied the said drawings, specifications, or other data is not to be regarded by implication or otherwise as in any manner licensing the holder or any other person or corporation, or conveying any rights or permission to manufacture, use or sell any patented invention that may in any way be related thereto.



UNEDITED ROUGH DRAFT TRANSLATION

PROBLEMS OF HEAT TRANSFER IN RAREFIED GASES

BY: L. Ye. Kalikhman

English Pages: 3

SOURCE: Russian Periodical, Soveshchaniye po Teplo 1 Massoobmenu, Minsk, 1961,

Tezisy Dokladov i Soobshcheniy, pp. 31-

32.

T-110 S/594-61-0-0-3-11

THIS TRANSLATION IS A RENDITION OF THE ORIGINAL POREIGN TEXT WITHOUT ANY ANALYTICAL OR EDITORIAL COMMENT. STATEMENTS OR THEORIES ADVOCATED OR IMPLIED ARE THOSE OF THE SOURCE AND DO NOT NECESSARILY REFLECT THE POSITION OR OPHNON OF THE POREIGN TECHNOLOGY DIVISION.

PREPARED BY

TRANSLATION DIVISION
POREIGN TECHNOLOGY DIVISION
WP-AFB, ONIO,

FTD-TT-62-978/1+4

Date 18 June 1963

PROBLEMS OF HEAT TRANSFER IN RAREFIED GASES

L. Ye. Kalikhman

The problems of convective heat transfer in rarefied gases are the same as in ordinary gas-dynamic conditions complicated by additional effects.

A decrease in the gas pressure leads first of all to a change in the surface conditions; a temperature jump and slippage on the wall occurs.

The processes of interaction of the flow with the surface depend essentially on the accommodation coefficient α and the coefficient of diffusion reflection σ .

The fundamental problem of convective heat transfer consists in determining the heat-transfer coefficients (the Stanton number St or the Nusselt number Nu) as functions of the parameters M, Re, Pr, T_{∞} , α , σ and the Knudsen number Kn = M/ $\sqrt[4]{Re}$.

Taking into account the effect of a temperature jump in Lees' solution for planar and axisymmetrical gas flows allows us to determine the effect of the Knudsen number on the Musselt number at the critical point, assuming thermodynamic equilibrium. With an increase in Kn the heat-transfer intensity decreases sharply.

In this case an increase in the enthalpy factor T_{ω} causes a remaining relation, while a decrease in T_{ω} causes a growth, in the heat flows. A decrease in the accommodation coefficient from $\alpha=0.8$ to $\alpha=0.4$ leads to an extremely sharp decrease in the heat-transfer intensity. These conclusions agree with Giedt's experiments carried out when $T_{\omega}=0.3$ and 0.7, when $M_{\infty}=1.32-5.7$, and $Re_{H}=30-80$.

In Giedt's experiments the Mach number has practically no effect; however, further increase of this number under low-pressure conditions should lead to freezing of the boundary layer. Consequently, the problem of heat-transfer due to recombination of atoms on the wall will be a critical one. This problem, which was sufficiently developed for a continuous medium in the works of Gulard and Rosner, has not yet been solved for rarefied gases, in view of the vagueness of the boundary conditions for an inhomogeneous gas.

We solved the problem of heat transfer of a longitudinally streamlined flat plate by two methods: the method of linearization of equations and the method of series expansion in a small parameter inversely proportional to the free path. In the region of large Kn both solutions coincide; in the region of small Kn, as was to be expected, the second solution is unsuitable. The solution obtained is a generalization of Schaaf's solution, indicating that under equilibrium conditions StM depends not only on Kn, but on the density ratio $\rho_{\rm S}/\rho_{\rm col}$. Calculations showed that, when Kn is constant, StM depends essentially on the Mach number and to a lesser degree on the enthalpy factor $I_{\rm col}$. Large temperature jumps on the surface correspond to high Mach numbers and $I_{\rm col}$ values essentially different from unity.

the effect i the lip velocity into account in the boundary contains for enthalpy stagnation and taking strict account of the effect of the work of the friction force in the expression for the heat flow pose certain difficulties. Calculations taking the above factors into account allow us to conclude that at large Kn and Mach numbers these effects are extremely significant.

In this case the heat flow is not proportional to the enthalpy drop $i_e - i_\omega$. Calculations showed that the heat-transfer intensity for a longitudinally streamlined plate is sharply reduced with a decrease in α and σ .

The extension of the results relating to planar flows of rarefied gas to the case of conical flows by means of a Stepanov
transformation is not feasible, due to the changes in the boundary
conditions. Direct calculations of the heat flows for this case yield
results coinciding with the experiments of Drake and Maslach.

(Moscow)

DISTRIBUTION LIST

DEPARTMENT OF DEFENSE	Nr. Copies	MAJOR AIR COMMANDS	Nr. Copies
HEADQUARTERS USAF AFCIN-3D2 ARL (ARB)	1 1	AFSC SCFDD DDC TDBTL TDBDP AEDC (ARY) BSD (BSF) AFFTC (FTY) ASD (ASYIM)	1 25 5 3 1 1 1
OTHER AGENCIES			
CIA NSA DIA AID OTS AEC PWS NASA ARMY (FSTC) NAVY NAFEC PGE RAND	1 6 9 2 2 2 1 1 3 3 1 12		

FTD-TT- 62-978/1+4